

aflutter

: a whimsical hair band :

Get inspired by a gorgeous print and feature it prominently on a one-of-a-kind headband. The possibilities are limited only by your imagination and fabric stash — have fun!



Time needed: 1/2 hour or less

Measurement: 20" around unstretched (easily adapted to fit any size head)

Here's what you need:

- pattern piece (found on page 3)
- less than 1/4 yard each of a main fabric and backing fabric
- lightweight fusible interfacing (I am using Pellon 911FF)
- chopstick
- fusible web (I am using Wonder Under)
- 3/8" elastic

Step 1: Do all your cutting first

Cut out the *aflutter* pattern piece and use it to cut:

- 1 piece in your main fabric
- 1 piece of the backing fabric
- 1 piece of the lightweight fusible interfacing
 - *** Trim 1/2" off both short ends of the interfacing piece as well as 1/4" off both sides (not the folded edge) - this will reduce bulk in the seams.
- You also need a 3"-4" piece of 3/8" elastic.



Step 2: Fuse the interfacing

- Center the interfacing on the backing fabric and fuse it according to the manufacturer's instructions.

Check it out —>

By trimming the interfacing as indicated above, you allow for the 1/4" seam allowances when you sew.





Step 3: Let's make the headband!

- Pin the main and backing pieces RS together.
- Stitch the length of both sides (*but NOT the ends*) using a 1/4" seam allowance.
- Backstitch at beginning and end.
- Turn the piece RS out. Take your time and use a chopstick to help with turning, if needed.
- Use that chopstick to smooth out and press into the seams from the inside.
- With a hot iron, press the RS and WS of the headband.
- Tuck both short ends toward the inside of the headband and press with an iron.
- Insert the 3/8" elastic into one end about 1/2" and pin in place.
- Edge stitch using a 1/8" seam allowance down both long sides as well as the short end with the elastic, securing it in place.
- Measure the headband on the wearer and make a mark to indicate placement.
- Edge stitch that final short end using a 1/8" seam allowance, securing the elastic in place.



Step 4: Now comes the fun part — appliqué!

- Apply the fusible web to the WS of your main fabric according to the manufacturer's instructions.
- Cut out your desired motifs.
- Remove the paper backing and fuse the appliques to the fabric.

The fabric I am using is a cotton lawn with a lovely translucence, so I was able to fuse on the RS directly on top of the exact same motifs. No worries if your fabric is more opaque — simply fuse your appliques to the WS of the fabric in a complimentary spot.

- Carefully cut out your appliques.
- Machine- or hand-stitch as many of the appliques to the headband where ever your heart desires.



Whip up a few headbands featuring your favorite prints or experiment with something new. Go vintage or modern — it's up to you.



Florals work especially well, too!



I hope you enjoy *aflutter*
as much as we enjoyed creating it!

Jennifer

